

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**




PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5 : F25D 25/00, A46B 13/00 B08B 9/20, B01J 13/02	A1	(11) International Publication Number: WO 92/15828 (43) International Publication Date: 17 September 1992 (17.09.92)
(21) International Application Number: PCT/US92/01610 (22) International Filing Date: 4 March 1992 (04.03.92) (30) Priority data: 663,567 4 March 1991 (04.03.91) US (71)(72) Applicant and Inventor: HERMAN, Norman, L. [US/ US]; 382 Ocean Avenue, Stratford, CT 06497 (US). (74) Agent: BAILEY, Ralph; Bailey & Hardaway, 125 Broadus Avenue, Greenville, SC 29601 (US). (81) Designated States: AT (European patent), BE (European patent), CA, CH (European patent), DE (European pa- tent), DK (European patent), ES (European patent), FR (European patent), GB (European patent), GR (Euro- pean patent), IT (European patent), JP, LU (European patent), MC (European patent), NL (European patent), SE (European patent).		Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: PROCESS OF PRODUCING SOFT ELASTIC GELATIN CAPSULES**(57) Abstract**

A safe and non-toxic process is provided for treating hot, newly formed soft elastic gelatin capsules (1) to avoid their sticking to one another and to remove matter in the form of oils, pastes, and solid particles from exterior surfaces of the capsules (10), comprising the steps of: 1) cooling the capsules (10) to aid in preventing capsule (10) deformation and to aid in removing aqueous moisture from exterior surfaces of the capsules (10), and 2) contacting the capsules (10) with an absorbent material (15) to remove the matter from the exterior surfaces of the capsules (10). Alternatively, for certain type capsules (10), the process of the present invention may comprise the single step of absorption (15) of matter from the exterior surfaces of the capsules (10).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FI	Finland	ML	Mali
AU	Australia	FR	France	MN	Mongolia
BB	Barbados	GA	Gabon	MR	Mauritania
BE	Belgium	GB	United Kingdom	MW	Malawi
BF	Burkina Faso	GN	Guinea	NL	Netherlands
BG	Bulgaria	GR	Greece	NO	Norway
BJ	Benin	HU	Hungary	PL	Poland
BR	Brazil	IE	Ireland	RO	Romania
CA	Canada	IT	Italy	RU	Russian Federation
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SN	Senegal
CI	Côte d'Ivoire	LI	Liechtenstein	SU	Soviet Union
CM	Cameroon	LK	Sri Lanka	TD	Chad
CS	Czechoslovakia	LU	Luxembourg	TG	Togo
DE	Germany	MC	Monaco	US	United States of America
DK	Denmark	MG	Madagascar		
ES	Spain				

PROCESS OF PRODUCING SOFT ELASTIC GELATIN CAPSULES

Background of the Invention

The present invention relates to soft elastic gelatin capsules and a method for producing such capsules which are free from surface oils or other unwanted material used in processing while providing for non-sticking of the capsules after formation. Such unwanted material may consist of liquid chemicals and solvents, such as naphtha and perchloroethylene, which are often used by manufacturers to remove processing oils and fluids but which are thought may be subject to environmental and health drawbacks.

Background Art

The field of the invention is generally referred to as Soft Elastic Gelatin Capsule Manufacturing, and the following references show the state of the art:

U.S. PATENTS

<u>Number</u>	<u>Name</u>	<u>Date</u>
961,936	Colton et al.	June 21, 1910
1,628,333	Schaub	May 10, 1927
2,349,430	Hiatt et al.	May 23, 1944
2,387,747	Cowley	Oct. 30, 1945
2,449,139	Power	Sept. 14, 1948
3,592,945	Engelking	July 13, 1971
3,656,997	Cordes	April 18, 1972
4,028,024	Moreland	June 7, 1977
4,670,287	Tsuji	June 2, 1987
4,816,259	Matthews et al.	March 28, 1989

PUBLICATION

5 L. Lachman, H. Lieberman & J. Kanig, The Theory and Practice of Industrial Pharmacy (3d ed. 1986) [hereinafter Industrial Pharmacy].

10 In soft elastic gelatin capsule technology, the media used for the casing of the capsule contains substances such as gelatin, water, glycerin, sorbitol, lecithin, pigments and starch. These substances are components which impart an elastic sheath around the drug, cosmetic, nutritional or other materials desired to be encapsulated. Due to the elastic, sticky nature
15 of the casing, very often capsules tend to adhere, attach, or stick together after they are just formed because of the characteristics of the gelatin-glycerin component mixture comprising the casing. These sticking properties have become the norm in
20 manufacturing operations.

Some methods of overcoming this sticking tendency contemplate using oils (ex., mineral), which promote sealing of the capsules and aid in preventing sticking. The capsules are thereafter subjected to a solvent wash
25 cycle. The wash cycle is an essential step of the soft elastic gelatin encapsulation process since it removes the oils. The capsules are then kept moving in a rotating pan, basket, or conveyance device while being

exposed to warm air to remove the solvents from the capsules. Such methods to remove oils possess inherent disadvantages.

First, the aforementioned rotating devices occupy a significant amount of operating space. Specifically, as many as ten separate, successive rotating baskets have customarily be used to remove the solvent remaining on the capsules from an initial wash cycle. Moreover, the conventional process moves the capsules to a second solvent washer after rotation in the tenth basket; the capsules are thereafter successively transferred to three additional rotating baskets to remove the solvent from the second wash cycle. Not only does such a process of treating newly-formed capsules occupy a large space, but it also demands considerable time, typically three to four hours.

Second, such wash cycles typically include the use of toxic organic liquids such as Perchloroethylene, Naphtha, Naphthalene, Toluene, Hexane, etc. For instance, Industrial Pharmacy, supra, at 407 teaches the use of a "Naphtha wash unit" to remove mineral oil from newly-manufactured capsules, and U.S. Patent No. 1,628,333 teaches the washing of completed capsules in a "suitable solvent" to cleanse them of the oil into which they were previously immersed to prevent

sticking. The organic liquid flushes the oils from the soft elastic gelatin capsule surface and acts to harden the capsule sheath or wall. The use of these liquids, however, poses potential environmental and health concerns.

Recent developments in soft elastic gelatin capsule technology include gelatin-mass bloom strength technology, which controls the ultimate degree of hardness of the soft elastic gelatin capsule, as disclosed in U.S. Patent No. 4,816,259; ingredient additions, such as a plasticizer as disclosed in U.S. Patent No. 2,349,430, or selective rationing of ingredients to increase physical and chemical compatibilities of the capsule fill material with the outside sheath or shell. However, as with the other attempts to perfect soft elastic gelatin capsules, the problem of removing the undesirable features of oil and matter from the capsule surface still remains.

Among other developments in the art is the cooling of newly-extruded capsules. For example, U.S. Patent No. 4,028,024 teaches cooling of capsules during conveyance thereof from an extruder head through the use of cool air blown through a foraminous conveyor belt. It is also taught, however, that when mineral oil is used in the manufacture of gelatin capsules, the

finished capsules must be subsequently washed of such oil. In general, none of the presently available processes are universally thought to provide for a clean, safe, environmentally sound production of soft elastic gelatin capsules.

In addition to all the other problems, the manufacturing of a soft elastic gelatin capsule at a manufacturer's plant frequently requires rewashing of soft elastic gelatin capsules after inspection for leakage for purpose of further removal of oils (ex., mineral, fish, vitamin E, soybean, etc.).

Thus, the industry has long sought a process which could be utilized after the formation of a soft elastic gelatin capsule which would provide the various desirable factors: non-sticking, sheen, no oil surface, product elegance, safe operational handling, environmentally safe operation and non-reactivity - while providing a handsome cost savings to the manufacturer, who currently must purchase expensive organic solvents and deal with potential OSHA and DHEC violations and personal illness due to solvent toxicity. Liability regulatory risks would be diminished with removal of solvent by a method which is recognized to be safe. The operators and handlers would then be free of the encumbrance of dealing with organic materials, and the health risks to the consumer

due to this factor would be eliminated. Reduction in the required operating area is also highly desirable.

Accordingly, it is an important object of the invention to provide a process of producing soft elastic gelatin capsules that will eliminate the need to use organic solvents for the removal of oils from the surfaces of such capsules.

Another important object of the invention is to provide a process of producing soft elastic gelatin capsules that will eliminate the need to subject such capsules to excessive rotation before undergoing surface oil removal, thereby reducing operating space requirements.

Another important object of the invention is to provide a process of producing soft elastic gelatin capsules that will utilize physical removal of surface oils and other matter from such capsules or a combination of such physical removal and temperature reduction of the capsules in varying, optimal ratios to achieve production of non-sticking, oil-free soft elastic gelatin capsules within the shortest possible time period.

Summary of the Invention

This invention relates to a process for treating hot, newly-formed soft elastic gelatin capsules to prevent their sticking to one another and to remove matter in the form of oils, pastes, and solid particles from the exterior surfaces of the capsules by the steps of: 1) cooling the capsules to aid in preventing capsule deformation and to aid in removing aqueous moisture from the exterior surfaces of the capsules, and 2) contacting the capsules with an absorbent material to remove such matter from the exterior surfaces of the capsules. Alternatively, for certain type capsules, the process of the present invention may comprise the single step of absorption of matter from the exterior surfaces of the capsules.

In another aspect, this invention relates to non-sticking, oil-free soft elastic gelatin capsules made by the foregoing process.

Capsules may be produced for internal or external use and may range from being a drug, nutritional supplement, cosmetic, or the capsule may act as a dosage form or device for the administration of pharmaceuticals, medicines, cosmetics, nutrients, drugs, pesticides or poisons. They may be inert,

containing no contents at all for gelatin supplement purposes, or be filled with potent liquids, solids or gases. This invention can be utilized for each type.

A preferred embodiment of this process
5 contemplates cooling capsules using cathebar air (air having low humidity) in conjunction with suitable lint-free modified polyester cloths. The capsules, after being formed, pass into a pneumatic transport conveyer and are thereby deposited into successive rotating
10 baskets wherein they undergo indirect heat exchange with cool cathebar air so that the capsule shell temperature is reduced adequately to prevent capsules from sticking to one another. The capsules simultaneously commingle with the modified polyester
15 cloths in the rotating baskets to physically remove surface oils.

The process of the invention is useful with capsules of all shapes, sizes and configurations. Capsule sizes which can be applied to the above
20 technology include but are not limited to #1, #2, #3, #4, #5, #6, #7, #8, #9, #10, #11, #12, #13, #14, #15, #16, #17, #18, #19, #20, #21, #22, #23. Capsules smaller or larger than those mentioned along with various shapes, configurations and applications should
25 be considered to be within the scop of this invention.

The process of the present invention will

eliminate the need for the toxic solvents and chemicals historically utilized in the preparation of soft elastic gelatin capsules, including but not limited to: Perchloroethylene, Naphthalene, Hexane, Dichloroethane, other hydrocarbons and halogenated solvents, and acetone. Hence, the scope of this invention will include elimination of all hazardous chemicals known to the industry in the procedure of manufacturing soft elastic gelatin capsules. As such, environmental pollution, human toxicity due to contact, and exposure with the chemicals will be eliminated. Processing plant liability would thereby diminish as it relates to the user of toxic chemicals in soft elastic gelatin capsule manufacturing operations. In addition, other anti-adherent materials, such as oils used as a physical aid to prevent sticking, can also be serviced by the process of this invention.

Brief Description of the Drawings

The invention will be more readily understood from a reading of the following specification and by reference to the accompanying drawings forming a part thereof, wherein an example of the invention is shown and wherein:

Figure 1 is a schematic view illustrating a manufacturing line to treat newly-formed capsules in accordance with a preferred embodiment of the process of the present invention.

Figure 2 is a partial enlargement of Figure 1, illustrating the preferred cooling means and the rotating tumbling means of the preferred embodiment of the process of the present invention.

Figure 3 is a schematic view illustrating the sequential stages of the cooling of newly-formed soft elastic gelatin capsules in accordance with an alternate embodiment of the process of the present invention.

Figure 4 is a plot of enthalpy versus temperature of a soft elastic gelatin capsule.

Figure 5 is a perspective view, shown partially in section, detailing the rotating tumbling means shown in Figure 2 and illustrating the progressive physical

removal of oil from soft elastic gelatin capsules as the capsules are deposited sequentially into a plurality of rotating baskets and then into a collection chamber.

5

Figure 6 is a schematic view detailing section D of Figure 3, into which carbon dioxide, both in liquid and in gaseous forms, is introduced to cool soft elastic gelatin capsules.

Description of Preferred Embodiments

In accordance with the present invention, it has unexpectedly been discovered that, by combining the cooling of soft elastic gelatin capsules after formation with the physical removal of outside oils and material therefrom, soft elastic gelatin capsules can be produced as free flowing, non-sticking entities without the use of solvents. The soft elastic gelatin capsules are cooled by the use of a refrigeration instrument in conjunction with an oil absorbent material in ratios which will vary depending on ingredients, capsule size, and composition. The degree of cooling and volume of oil absorbent material therefore vary with the product being manufactured. Moreover, different types of cooling and various physical materials for oil removal can be employed; for instance, small amounts of cooling and minimal fiber material can be instrumental in production of elegant soft elastic gelatin capsules.

Soft elastic gelatin capsule cooling and physical removal of oils and matter are combined in particular amounts depending upon the product and product nature. The ranges of cooling and material required for physical oil removal are: 1) for capsule cooling,

sufficient cooling to reduce the initial capsule temperature of 70-95°F (21.1-35.0°C) to 35-45°F (1.7-7.2°C)., and 2) for physical removal of oil, between one small swatch of fiber to massive amounts of cloth material. The oil absorbency will be dependent upon the quantity of oil to be absorbed and the presence of other external materials such as powders.

Additionally, the volume of cloth material will be determined by the number of capsules and the sizes thereof. Such cloth may be reused.

Capsule cooling helps to prevent capsule deformation, helps to remove aqueous moisture from the capsule shell, and allows for non-sticking of the capsules prior to de-oiling. The range of cooling temperature depends upon the machinery and orientation of the soft elastic gelatin capsule apparatus. Input temperature (the temperature of the capsules prior to cooling) may vary depending upon whether the cooling is to be applied directly or indirectly on the capsules or gelatin. Typical gelatin capsule fill content temperature is 60°F (15.6°C) to 95°F (35.0°C). Cooling of the capsule may require a temperature drop of as little as 1°F (17.2°C), or as much as 100°F (37.8°C), although these extremes are not the recommended magnitudes for most kinds of capsules.

Cooling of the capsules should be applied at a rate which is in accord with the thermal heat transfer rate of the individual capsule. As capsules are produced in various shapes and sizes ranging from very small to quite large, the degree of heat transfer across the capsule wall will vary, thus requiring a lower or higher level of cooling to prevent sticking prior to de-oiling. The temperature of capsule contents will significantly influence the designated cooling temperature. Some capsule contents are heated prior to manufacturing to facilitate filling and proper sealing of the capsule. Those capsules, being necessarily warm, require a higher rate of cooling than those capsules whose contents are not pre-warmed. Another factor which will play a role in the degree of cooling is gelatin ribbon thickness. Those capsules having a ribbon thickness which is greater than others will require a higher rate of cooling. Exceptions to the above are possible.

Cooling can be achieved in various ways. Refrigeration by the use of mechanical or electronic devices, forced air, or outside cool or cold air blown onto the system directly or indirectly can achieve the desired results. A refrigeration unit in the configuration of a blower, conveyor, or box unit can

also achieve the cooling results. Water-cooled conveyance units or jacketed machinery may also bring about the desired results of cooling the capsules. Any other physical or chemical (non-toxic) cooling technique which brings about the successful cooling of soft elastic gelatin capsules can be thought of as being within the scope of this invention.

The preferred method of cooling contemplates the use of cathebar air to foster direct heat exchange with the capsules to cool them. Such air additionally drives off any surface moisture due to condensation. Figure 1 illustrates a manufacturing line generally comprising an extruder head A, a cup C, a suitable pneumatic conveyor 3, and a rotating tumbling means 4. After capsules are formed by the extruder head A, they drop into cup C, whereupon they are transported by the pneumatic conveyor 3 to the rotating tumbling means 4. Referring to Figure 2, the rotating tumbling means 4 is illustrated as being a series of rotating baskets 13, each basket housed in a suitable cabinet 5 and containing at least one absorbent cloth 15, such as modified polyester, for intermingling with capsules 10. Each basket 13 is provided with a plurality of baffles 9 to encourage tumbling of the capsules. Cathebar air having a relative humidity of approximately 20% enters

16

the cabinets from the rear of same (not shown). The breakaway section reveals a cooling coil 6 with incoming cathebar air at 65-70°F (18.3-21.1°C) indicated by arrows 7, flowing therethrough. The resulting cathebar air, indicated by arrows 8, has been cooled to 45-50°F (7.2-10.0°C) by coil 6 and passes through the underside of basket 13. Basket 13 has a plurality of holes therein (not shown) to permit passage of the cool cathebar air 8 into its interior, thereby allowing direct heat exchange with the capsules 10. This heat exchange reduces the capsule input temperature by 30-40°F over a time of one to sixty minutes.

Another cooling method contemplates direct heat exchange with solid carbon dioxide. Carbon dioxide or other gases converted to solid CO₂ mist by the mixture of liquid and gaseous forms can achieve ultimate capsule cooling. Figure 3 illustrates the progression of soft elastic gelatin capsules through a CO₂ cooling system. Vitamin E capsules are taken as an illustrative example. For further example, in this embodiment, forming dies A enclose the vitamin E oil in a gelatin sheath. The formed capsules drop into a cup C and then enter a pneumatic transport driven by a suitable blower B. At point C, the capsul input

17

temperature is about 75°F (23.8°C). The capsules are conveyed to a section D, into which the liquid-gas carbon dioxide mixture is introduced (see Figure 6). The pipe temperature of section D is approximately -100°F

(-87.6°C). The capsules are further conveyed to a pipe E, which has a temperature of about -70°F (-70.9°C).

Once the capsules exit piping E and are deposited onto a suitable conveyor F, the capsules are at a temperature of approximately 45°F (7.2°C), which is considered the optimum output temperature for vitamin E capsules. This cooling method can reduce capsule temperature from 70-95°F (21.1-35.0°C) to 35-45°F (1.6-7.2°C) over a time of less than two seconds. A

ventilation duct G may be disposed above the conveyor F to remove excess carbon dioxide. Experimental results have indicated that temperature in the vent G is about 30°F (1.1°C), indicating that most of the carbon dioxide is utilized for the purpose of capsule heat reduction.

Jacketed coolant systems are efficient and can accomplish soft elastic gelatin cooling properties through indirect heat exchange with CO₂ mist. Specifically, the section D pipe may be enclosed within a jacket, and CO₂ mist may be introduced into the

annular space between section D and the jacket. The mist would cool the section D pipe, which, in turn, would cool the capsules passing therethrough.

Regardless of the cooling method used, capsules should be cooled sufficiently to prevent sticking but not excessively so as to offset capsule shock or possible distortion and quick contraction. Some typical examples of desirable capsule cooling in accordance with the process of the present invention are:

- (a) Input temperature after capsule formation 75°F (23.8°C). Output temperature after cooling of the capsules 45°F (7.2°C).
- (b) Input temperature after capsule formation 90°F (32.2°C). Output temperature after cooling of the capsules 40°F (4.4°C).
- (c) Input temperature after capsule formation 80°F (26.7°C). Output temperature after cooling of the capsules 35°F (1.6°C).
- (d) Input temperature after capsule formation 65°F (18.3°C). Output temperature after cooling of the capsules 50°F (10.0°C).
- (e) Input temperature after capsule formation 0°F (-17.8°C). Output temperature after cooling of the capsule -50°F (-59.8°C).

Thermal heat transfer studies have indicated that 15-20 British Thermal Units/lb. of cooling are required

to sufficiently cool capsules. This figure has been derived from the plot of enthalpy versus temperature of a soft elastic gelatin capsule, illustrated in Figure 4. For a preferred drop in capsule temperature, for example, from 75°F to 45°F, the corresponding change in enthalpy is approximately 15 Btu/lb. The process of the present invention therefore contemplates cooling a capsule surface for a time sufficient to remove about 10-20 Btu/lb. from a capsule ranging from as small as #1 oval to as large as #20 oblong.

These Examples should not be thought of as being the only ranges of temperature within the scope of this invention. Temperatures above or below the inputs and outputs can be construed to be included in the operational range of this invention.

In the case of lecithin oil capsules input temperature after formation of the sealed soft elastic gelatin capsule is about 85°F (29.5°C). Sufficient cooling is utilized to reduce the capsule temperature to about 45°F (7.2°C). Once established, this temperature deflection can be keyed into a thermocouple, which regulates the necessary and required cooling capacity. Lecithin capsules which are #20 oblong in dimension are somewhat representative of a large gelatin capsule. Other products which can be

encapsulated include paste products such as drugs, amino acids, fish oils, plant oils, fragrances, and medications for internal or external application.

The preferred cooling system is one which can be easily controlled as to the degree of temperature imparted to the capsules while the preferred fibers used to remove oil and extraneous matter from capsule surfaces are those which can be recycled numerous times and which have a large affinity for oils. A typical, preferred cooling and oil removal process has the following specifications.

Input Temperature	-	70-95°F (21.1-35.0°C)
Retention time during cooling	-	Sufficient for capsule surfaces to chill from 35-45°F (1.6-7.2°C).
Contact time during oil removal	-	Dependent upon volumes of oil being left on the capsules. The number of oil absorbent cloths can be determined by the cleanliness of the capsules.

The physical removal of oils is preferably accomplished by placing the capsules within the rotating baskets previously described in connection with use of the cathebar air cooling system. Referring to Figure 5, oily capsules 10 pass through a suitable conveyor 3 in the direction shown by arrow 12 and are

21

deposited into a basket 13 rotating in a direction such as indicated by arrows 14. In this particular variation of the process of the present invention, the capsules intermingle with oil absorbent cloths 15 for preliminary physical removal of oil. The rotating baskets may alternatively be lined with oil-absorbent material instead of containing oil absorbent cloths. Capsules remain in basket 13 until they are displaced by the influx of additional capsules from conveyor 3. The displaced capsules flow in the direction shown by arrow 16 into another rotating basket 13' adjacent to basket 13. There the capsules undergo further physical removal of oil by oil absorbent cloths 15 until displacement into rotating basket 13'', where still further physical removal of oil occurs. Displacement of capsules from one rotating basket to another may be promoted by progressively declining the elevation of each basket, here from the left to the right of Figure 5. When the capsules are thereafter displaced into a collection chamber 17, they are oil free and are ready for drying. This preferred method of oil removal, when combined with the introduction of cool cathebar air, reduces treatment time of newly-formed capsules from the conventional 3-4 hours to approximately 30-45 minutes. Moreover, this method saves a considerable

amount of space required for treatment of newly-formed capsules when compared to conventional methods. For instance, only three rotating baskets and a collection chamber are required for this embodiment, as compared with thirteen rotating baskets and two solvent washers for a conventional process.

It has been found that cooling can prevent sticking of capsules. Where carbon dioxide mist was applied directly onto conveyed pre-formed soft elastic gelatin capsules as described in the above text referring to Figure 3, the capsules became cool sufficiently so as not to stick together and were further conveyed to rotating baskets. In the baskets were cloths made of oil absorbent modified polyester. The capsules rolled with the cloths for a sufficient time to allow for oil removal. In some cases oil was picked up satisfactorily within five to twenty minutes. Times varied depending on oil quantities.

Another application involved the movement of soft elastic gelatin capsules from the point of formation to a static bed refrigerator. Less than sixty (60) second retention at 33-50°F (0.6-10.0°C), preferably 40°F (4.4°C), accomplishes the task of preventing capsule-to-capsule sticking. The capsules were then placed on trays lined with oil absorbent fabric.

Cooling of the capsules can take place at the same time the oil is being removed. In addition to the preferred process method (Figures 1, 2, and 5), such an operation may comprise rotating baskets, such as those illustrated in Figures 2 and 5, which are exposed to solid CO₂ mist in a manner similar to section D of the apparatus illustrated in Figure 3. The capsules would therefore undergo indirect heat exchange with solid carbon dioxide while undergoing physical removal of oil. This particular operation can reduce the capsule input temperature by 30-40°F over a time of no more than 30 seconds.

Finally, it is to be understood that, for certain type capsules, the process of the present invention may comprise the single step of physically removing the oil and other matter from the capsules. For example, a series of rotating baskets may be used to remove oils from the capsules without a cooling means, although minor sticking tendencies would appear in the capsules at early stages of oil removal. Although some oil would be present on the finished capsules, it would be an adequately low amount for certain types of capsules, and the use of solvents would still be eliminated.

It is therefore seen that cooling of the capsule can be direct or indirect, and oil removal can be

accomplished by using loose fibers, intact cloth, absorbent cellulose, absorbent paper and other man-made or synthetic materials which have affinity for oil. The conditions of oil absorption control the reusability of the absorptive material and duration of use. Reusable fibers are available which can be washed and repeatedly applied. Disposable materials are also commercially available. The choice depends on the user's interest and facilities.

5

Best Mode for Carrying Out the Invention

In order that those skilled in the art may be better enabled to practice the present invention, the following examples are given by way of illustration and not by way of limitation.

10

Example 1

A formed capsule was delivered directly to a pneumatic transfer conveyer equipped with a blower sufficiently capable of moving capsules along a 12 foot length. Referring to Figure 6, a Praso valve feeds a mist of carbon dioxide onto the capsules at section D (from Figure 1), after the point at which capsules are picked up by the pneumatic transport. It is important that the carbon dioxide be created by an admixture of liquid and gaseous forms of carbon dioxide. The

15

20

25

gaseous and liquid forms of carbon dioxide are fed to Praso valve 20 through respective conduits 21 and 22. The amount of gaseous and liquid carbon dioxide flowing to Praso valve 20 is controlled by respective suitable valves 23 and 24. The combination results in a solid which can be controlled in terms of particle size by a Praso valve regulator 25. An identical arrangement to that described above may be used to inject additional carbon dioxide admixture into section D, as indicated at 20'. Although transport time is less than one second, capsule temperature drops from a formation temperature of about 85°F (29.5°C) to one of 45°F (7.2°C) after conveyance. Capsule output can range from less than one thousand to over three thousand capsules per minute. The capsules are transported to rotating baskets which contain oil absorbent cloth in a size that agrees with manufacturing parameters. They are retained in such baskets until sufficient oil, pastes, and/or solid particles have been removed. The capsules are then dried; for example, they are placed on paper-lined trays and are further processed by drying and inspection.

The drying and inspection, a necessary step in the total manufacturing process, may constitute additional steps of the process of the present invention. One

drying method, for example, contemplates maintaining capsules at a low-humidity condition in a chamber with forced air circulation to allow for uniform drying. The chamber may be rotating or static, and the volume of forced air may vary. It has been suggested that drying time may in some cases be accelerated by cooling the capsules through the various methods described herein. Typically, soft elastic gelatin capsules require static bed drying for 12 to 16 hours. Using the process of the present invention, capsules can dry in less than 4 hours, although certain other types of capsules may take several days to fully dry. Oil absorbent material can be additionally implemented to further remove matter from the capsules after the drying and inspection thereof.

Example 2

In a manner similar to that described in Example 1, except that pneumatic transport was not used, capsules were cooled using dry ice to cool a rolling conveyor onto which capsules were placed. The same results were obtained.

Example 3

In a manner similar to that described in Example 1, the same cooling of capsules was done except that capsules were placed directly onto trays lined with oil

absorptive cloth. The same results were obtained.

Example 4

In a manner similar to that described in Example 1, cooling of capsules was done such that capsule temperature drop was from 85°F (29.5°C) to 60°F (15.6°C). The process yielded the same results.

Example 5

In a manner similar to that described in Example 1, cooling of capsules was done such that capsule temperature drop was from 85°F (29.5°C) to 33°F (0.6°C). The process yielded the same results.

Example 6

In a manner similar to that described in Example 1, oil removal was accomplished by the use of only one cloth, and observed oil and surface material was deemed removed as was with three cloths.

Example 7

Physical removal of oil and other matter from the capsules was done in a manner similar to that described in Example 1, but cooling was accomplished through direct heat exchange with cathebar air as per the preferred embodiment. Capsules were successfully processed with only minor sticking tendencies.

Physical removal of matter, particularly oils, from the capsules can be additionally accomplished by

tumbling or rolling the capsules on a bed of oil-absorbent material, or by placing them on a static bed of the same material.

5 The above examples show that the Soft Elastic Gelatin Capsule Solvent Elimination Process performed according to the present invention can be applied under a wide variety of conditions. In general, the process can be incorporated with any active or inactive medicinal or food nutrient, cosmetic, novelty or
10 toiletory product.

RESULTANT CAPSULES

 The soft elastic gelatin capsules produced according to the process of the present invention using various methods as illustrated above were subjected to
15 stability studies and transportation tests after storage. The resultant capsules were bulk packaged and stored in a warehouse environment for several weeks. A bulk packed box of these capsules was shipped under separate cover of a bulk box of soft elastic gelatin
20 capsules produced using the conventional manufacturing process, i.e., a solvent wash. The land and air shipment did not undergo any special handling instructions and was subjected to high heat and humidity conditions by movement to and from South
25 Florida. The returned capsules were examined by a Quality Control specialist and by manufacturing heads.

The capsules that underwent the inventive process were free flowing and oil free. Those capsules that went through a solvent wash, however, were clumped and tended to stick to one another.

5 While a preferred embodiment of the invention has been described using specific terms, such description is for illustrative purposes only, and it is to be understood that changes and variations may be made without departing from the spirit or scope of the
10 following claims.

What is Claimed Is:

1. A process for treating newly formed soft elastic gelatin capsules to avoid their sticking to one another and to remove matter in the form of oils, pastes, and solid particles from exterior surfaces of said capsules, comprising the steps of:

cooling said capsules to aid in preventing capsule deformation and to aid in removing aqueous moisture from exterior surfaces of said capsules; and

contacting said capsules with an absorbent material to remove said oils, pastes, and solid particles from said exterior surfaces of said capsules.

2. The process set forth in claim 1 wherein said absorbent material is modified polyester cloth.

3. The process set forth in claim 1 wherein cooling is accomplished by direct heat exchange with solid carbon dioxide.

4. The process set forth in claim 3 wherein said cooling of said newly formed soft elastic gelatin capsules reduces temperature thereof from 80-90°F (26.7-32.2°C) to 33-60°F (0.6-15.6°C) over a time of less than one second.

5. The process set forth in claim 1 wher in cooling is accomplished by indirect heat exchange with solid carbon dioxide.

5 6. The process set forth in claim 5 wherein said cooling of said newly formed soft elastic gelatin capsules reduces temperature thereof from 80-90°F (26.7-32.2°C) to 33-60°F (0.6-15.6°C) over a time of less than one second.

10 7. The process set forth in claim 1 wherein cooling is accomplished by direct heat exchange with cathebar air.

15 8. The process set forth in claim 7 wherein said cooling of said newly formed soft elastic gelatin capsules reduces temperature thereof by a magnitude of 30-40°F.

9. The process of claim 1 wherein cooling is accomplished by using a static bed refrigerator.

20 10. The process of claim 9 wherein said newly formed soft elastic gelatin capsules are retained in said static bed refrigerator at 33-50°F (0.6-10.0°C) over a time of less than 60 seconds.

11. The process set forth in claim 1 wherein said newly formed soft elastic gelatin capsules are

contacted by said absorbent material in a rotating tumbling means.

5 12. The process set forth in claim 11 wherein said rotating tumbling means is a plurality of rotating baskets, each of said baskets containing at least one cloth of oil-absorbent material for intermingling with said newly formed soft elastic gelatin capsules.

10 13. The process set forth in claim 11 wherein said rotating tumbling means is a rotating basket lined with said absorbent material.

 14. The process set forth in claim 1 wherein said newly formed soft elastic gelatin capsules are tumbled on a bed of said absorbent material for removing said matter from exterior surfaces of said capsules.

15 15. The process set forth in claim 1 wherein said newly formed soft elastic gelatin capsules are placed onto a static bed of said absorbent material for removing said matter from exterior surfaces of said capsules.

20 16. The process set forth in claim 1 wherein said newly formed soft elastic gelatin capsules are simultaneously cooled and contacted with absorbent

material.

17. The process set forth in claim 16 wherein said newly formed soft elastic gelatin capsules are intermingled with said absorbent material within a rotating tumbling means while undergoing indirect heat exchange with solid carbon dioxide.

18. The process set forth in claim 17 wherein said cooling of said newly formed soft elastic gelatin capsules reduces temperature thereof by a magnitude of 30-40°F over a time of no more than 30 seconds.

19. The process set forth in claim 16 wherein said newly formed soft elastic gelatin capsules are intermingled with said absorbent material within a rotating tumbling means while undergoing direct heat exchange with cool cathebar air.

20. The process set forth in claim 19 wherein said cooling of said newly formed soft elastic gelatin capsules reduces temperature thereof by a magnitude of 30-40°F.

21. The process set forth in claim 20 wherein said absorbent material is modified polyester cloth.

22. The process set forth in claim 1 wherein said

newly formed soft elastic gelatin capsules are cooled from 70-95°F (21.1-35.0°C) to 35-45°F (1.6-7.2°C) over a time of less than two seconds by indirect heat exchange with carbon dioxide mist and contacted with said absorbent material in a rotating tumbling means.

23. The process set forth in claim 22 wherein said absorbent material is modified polyester cloth.

24. The process set forth in claim 1 including the further steps of drying and inspecting the thus-produced capsules.

25. The process set forth in claim 24 wherein said capsules are dried after about 4 hours.

26. The process of claim 1, wherein the surfaces of the capsules are cooled so as to remove about 15-20 Btu/lb. from a capsule ranging from as small as #1 oval to as large as #20 oblong.

27. A process for treating newly formed soft elastic gelatin capsules to avoid their sticking to one another and to remove matter in the form of oils, pastes, and solid particles from exterior surfaces of said capsules, comprising the steps of:

cooling said capsules sufficiently to aid in

preventing capsule deformation and to aid in removing aqueous moisture from exterior surfaces of said capsules; and

5 removing said oils, pastes, and solid particles from the exterior surfaces of said capsules.

10 28. A process for treating newly formed soft elastic gelatin capsules to avoid their sticking to one another and to remove matter in the form of oils, pastes, and solid particles from exterior surfaces of said capsules, comprising the step of contacting said capsules with an absorbent material to remove said oils, pastes, and solid particles from said exterior surfaces of said capsules.

15 29. The process set forth in claim 28 including the further steps of drying and inspecting the thus-produced capsules.

20 30. The process set forth in claim 29 wherein said absorbent material is used to further remove said matter from exterior surfaces of said capsules after said capsules have been dried and inspected.

31. Soft elastic gelatin capsules, prepared by the process of claim 1.

36

32. Soft elastic gelatin capsules, prepared by the process of claim 19.

33. Soft elastic gelatin capsules, prepared by the process of claim 22.

5 34. Soft elastic gelatin capsules, prepared by the process of claim 27.

35. Soft elastic gelatin capsules, prepared by the process of claim 28.

10 36. The process set forth in claim 27, wherein the removing of matter in the form of oils, pastes, and solid particles from the exterior surfaces of said capsules is accomplished by absorbing said matter from said exterior surfaces.




Fig. 1.

2/6




Fig. 2.

3/6






Fig. 3.

4/6

*Fig. 4.*

SUBSTITUTE SHEET

Fig. 5.



SUBSTITUTE SHEET

6/6





Fig. 6.

INTERNATIONAL SEARCH REPORT

International Application: PCT/US92/01610

I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all) ⁶		
According to International Patent Classification (IPC) or to both Mayansal Classification and IPC IPC (5): F25B 25/00 A48B 13/00 B08B 9/20 B01J 13/02 US CL: 62/62,381; 15/4; 134/25.1, 40; 264/4.3		
II. FIELDS SEARCHED		
Minimum Documentation Searched ⁷		
Classification System	Classification Symbols	
U.S.	62/62, 381; 15/4; 134/25.1, 40; 264/4.3	
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched ⁸		
III. DOCUMENTS CONSIDERED TO BE RELEVANT ⁹		
Category ⁹	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³
A	US,A, 458,571 (Gedge) 1 September 1891 see the entire document	28-30,35
A	US,A, 3,137,630 (Hecker et al) 16 June 1964 see the entire document	1-27, 31-34 36
A	US,A, 3,576,759 (Powell et al) 27 April 1971 see the entire document.	1-27, 31-34 36
A	US,A, 3,797,272 (Huey) 19 March 1974 See the entire document	1-27 31-34 36
A	US,A, 4,978,483 (Redding, Jr.) 18 December 1990 See the entire document	1-27 31-34 36
A	US,A, 5,017,383 (Ozawa et al) 21 May 1991 See the entire document	1-27 31-34, 36
<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>¹⁰ Special categories of cited documents: ¹⁰</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="width: 45%;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"A" document member of the same patent family</p> </div> </div>		
IV. CERTIFICATION		
Date of the Actual Completion of the International Search		Date of Mailing of this International Search Report
27 May 1992		66 JUL 1992
International Searching Authority		Signature of Authorized Officer
ISA/US		 Ronald C. Capossela

FURTHER INFORMATION CONTINUED FROM PREVIOUS SHEETS

I. CLASSIFICATION OF SUBJECT MATTER:
IPC (5):

ICP (5): F25D 25/00 A46B B08B 9/20 B01J 13/02
U.S. CL: 62/62, 381; 15/4; 134/25.1, 40; 264/4.3

VI. OBSERVATIONS WHERE UNITY OF INVENTION WAS LACKING
This ISA found multiple inventions as follows:

- I. Claims 1-27, 31-34 and 36 drawn to methods of treating capsules by cooling and removing particles from the exterior surfaces thereof classified in class 62/62
- II. Claims 28-30 and 35 drawn to a method of removing particles from the exterior surfaces of capsules by direct contact with an absorbent material classified in class 134/25.4